

AR55 - Dual Power Supply - 2x0-15V; 2x0-5A

section	1	2
output voltage (V)	0 ÷ 15 Vcc	0 ÷ 15 Vcc
output current (A)	0 ÷ 5 Amp	0 ÷ 5 Amp
current continuous service to the maximum voltage(A)	3 Amp	3 Amp
digital output meter	3digit + 3digit	
input voltage	230 Vca ±10%50Hz	
operating temperature	-10C° ÷ +45C°	
mains protection	Fuse	
output protection	electronic	
output stability	± 0,1V	
ripple	3mV	
main-output insulation	V=2,5V1' R >100Mohm	
dimensions: (w, h, d)	200, 120, 325 mm	
weight	5,50 Kg	



The 'PROFESSIONAL' power supplies to variable voltage are the ideal combination for use in electronic workshops, plates repair in the information technology sector, teaching and servicing.

- Particularly suitable for feeding apparatuses to non-standard voltage.
- Series or common-zero connection options.
- Adjustable output voltage.
- Protection against short circuits and overloads by means of current limitation, adjustable from zero to I max.
- Display of voltage or output current on high brilliance ½ inch display unit.
- Facility for constant current operation, important when recharging storage batteries.
- Constructed with discrete components and standard integrated circuits in order to facilitate servicing.

Metal case with epoxy resin finish.