

MA 2405 DECADE CAPACITOR BOX

Description

The MA 2405 consists of three decades made of high-quality tropicalised styroflex capacitors with accuracy ±1%.

Capacitance values on output terminals can be set from 100pF to 100.000pF in steps of 100pF with three selector switches.

Switches and capacitors are protected by a special internal housing, connected to a common terminal of all capacitors (central terminal) and fastened to the outer housing over insulation plates. Capacitance between both housing is 100pF ± 2% and is not added to the decade capacitance except when the upper terminal is connected to the external housing.

The extremely high dc insulation resistance of the MA2405 allows the device to be used in dc circuits. Permitted operating voltage corresponds to most requirements occurring in everyday practice.



For discharging the capacitor a pushbutton "discharge" is used which connects the switched-on capacitor to earth via a 100 K Ω resistor.

Technical data

Capacitance range	100100.000 pF	Max frequency	
-Three decades		X 100 pF	9 MHz
X 100 pF	1001.000 pF	X 1000 pF	2 MHz
X 1.000 pF	1.0009.000 pF	X 10000 pF	500 KHz
X 10.000 pF	10.00090.000 pF	Permitted max	400 V dc - 250 V ac
Accuracy	±2%	operating voltage	
Loss angle (tgδ)			
X 100 pF	max 5x10 ⁻⁴ at	Test voltage against	1.5KV ac
	100KHz	external housing	
X 1.000 pF	max 4x10 ⁻⁴ at 10KHz	Capacitance between	100 pF ±2%
		both housing	
X 10.000 pF	max 4x10 ⁻⁴ at 1KHz	Insulation resistance	min 10000 M Ω
Dimensions (LxHxW)	205 X 85 X 175 mm	Capacitor discharging	over resistor 100 K Ω
Weight	1.35 Kg		with pushbutton
			"discharge"

Copyright © italtec s.r.l. All Rights Reserved

Ci riserviamo di apportare modifiche e migliorie senza preavviso We reserve the right to change these specifications without notice Photos et données techniques susceptibles de modifications sans avis ITALTEC S.R.L. SISTEMI TECNICI DIDATTICI 20090 FIZZONASCO MI (Italy) – Via privata Liguria, 3 Tel. +39 02-90.721.606 Fax. +39-02-90.720.227 e-mail: italtec@italtec.it http://www.italtec.it