

## DC WOUND SHUNT MACHINE

Company with Quality Management System Certified by DNV = ISO 9001/2008 =

# MOD.3140

### Technical specifications

Industrial, complete with base plate, provided with silk screened terminal board and with 4mm safety sockets.

Modes: Motor Self- and ext. excited gen.

Nominal voltage: **220Vdc** 

Current: **1,5A** 

Excitation voltage: **220Vdc** 

Nominal power: 250W (as motor) 200W (as generator) Other power on request

Nominal speed: 3000 rpm

Dimensions: (LxWxH) 35x18x25cm

*Weight.* **9,5 kg** 

CE

#### General

The SHUNT motor, if supplied with constant voltage, runs at constant speed. This machine is then used when a constant speed is required in the application; typical use of this machine are machine tools, pumps and for rolling mills.

- Manual explaining theory and practice for laboratory experiments.
- Imprinted terminal boards with the synoptic.
- All connections on 4 mm safety sockets included thermal contact.

As indicated on the silk screened terminal board, the machine windings are:


- 1 A1-A2 rotor winding (Armature)
- 2 E1-E2 excitation winding

#### **Didactical purpose**

- Reversing the rotation direction
- Direct test for mechanical characteristic (torque as function of the speed)
- Direct test for electro-mechanical characteristic (torque, speed, input current, efficiency as function of the output power)



- Base plate with four rubber feet.
- With coupling cog for easy engagement with other machine.
- Protection against thermal overload.



- Motor connection
- Typical machine data evaluation
- Measurement of the windings resistance
- Unload test of the motor
- External characteristic determination for a DC generator
- Regulation characteristic determination for a DC generator

#### **Options**

Depending on the specific requirements of the application the machine can be provided with two shaft ends, with other power values and can be designed with the appropriate number of poles in order to have the required nominal speed. (MOD.3140-4: 4 poles DC shunt machine 1500 rpm).

#### Accessories:

A full range of accessories and options are available like electromagnetic brakes, powder brakes, measuring modules such as voltmeter, ammeter power meter, connection cables and power supplies



Starting rheostat MOD.3010

Excitation rheostat MOD.3012



Resistive load for DC generator MOD.3016-R



Speed control with SCR for DC machine MOD.3230

#### Copyright © 2008 – italtec T.T.S. Srl All right Reserved

Ci riserviamo di apportare modifiche e migliorie senza preavviso We reserve the right to change these specifications without notice Photos et données techniques susceptible de modifications sans avis

#### italtec Technical Training Systems S.R.L.

20129 - MILANO - ITALIA - Viale Regina Giovanna, 35 Tel. +39 02 90 721 606 - Fax. +39 02 90 720 227

e-mail: italtec@italtec.it www.italtec.it